

MODEL	PA-1260/ PA-1400/ PA-1680/ PA-11000 SERIES
Power supply	AC: 110-120V, 60Hz; AC: 220-240V, 50Hz
Power output (Load at 4Ω)	PA-1260: 260W (RMS), PA-1400: 400W (RMS) , PA-1680: 680W (RMS) , PA-11000: 1000W (RMS)
Frequency response	30Hz~18kHz (− 3dB)
Input sensitivity	Input 1-4: − 52dB under Balanced input; − 49dB under Unbalance input; − 10dB under line input; Input 5: 0/ − 10dB under AUX input;
Tone control	Bass: 100Hz±10dB Treble: 10kHz±10dB
Distortion (T.H.D.)	< 0.5%
S/N ration	AUX≥75dB, MIC≥65dB
Output impedance	4Ω, 8Ω, 25V, 70V, 100V
Constant Voltage output	25V, 70V, 100V
Siren function	YES
VU-meter (LED)	YES
Telephone paging select function	YES
Priority function of Mic.1	YES
2-TONE CHIME	YES
Cassette module	Frequency response: 50~12kHz, S/ N ratio: ≥45dB THD: ≤1% Controls: Auto reverse, F. Skip/FF, B. Skip
Digital tuner module (TM-100)	Receive range: FM: 87.5~108MHz AM: 525~1650kHz Sensitivity: FM: 2.5SuV/ AM: 20uV S/N ratio: FM: 65dB/ AM: 50
CD player module	Slot-loading CD player(with MP3 reader function) Digital ELECTRONIC-SHOCK PROTECTION function 40 sec Anti-shock for Audio CD 120 sec Anti-shock for MP3 (128Kbps) MP3 Bit Rate: 8 ~ 320 K MP3 playback: ISO9660, Joliet format compatible S/N Ratio:>75dB CHANNEL SEPARATION:>70dB T.H.D.:>0.2% (@1KHz/0dB,ESP OFF) Ferquency response: 20Hz-20KHz (+0.5/-2dB)
PHANTOM VOLTAGE	INPUT1-4 48V
Dimensions (W×D×H)	483×444×133mm (19"×17.5"×5.2")
Weight	PA-1260: 12kg (26.46 lb) , PA-1400: 14kg (30.87 lb) , PA-1680: 14kg (30.87 lb) ,PA-11000: 19.5kg (43 lb)

