

SA-9120CDT

- RMS 90W/120W
- Compact CD player. (With USB+MP3 reader function)
- Digital LCD display Tuner.
- Over load & over current protection.
- Speaker rely protection
- Low distortion and noise level.

MODEL	9120CDT
Power output	120W
Frequency response	50Hz~15kHz
Power supply	AC 110-120V/ 220V-240V, DC 24V
Inputs impedance	AUX: 47K Ω Mic – 1~4: 500-1K Ω (BAL.)(LO/ HI) Mic – 1 (UNBAL.): 10K Ω Line in: 0dB/1V
Tone control	Bass: 100Hz \pm 10dB Treble: 10kHz \pm 10dB
Total harmonic distortion	less than 1%
Output impedance	Com 4, 8, 16 Ω 70, 100V

S/ N ratio	Mic ≥ 60 dB AUX ≥ 75 dB
Antenna type	FM: 75 Ω unbal AM: loop ant
Tuner module	FM: 87.5~108MHz AM: 525~1650kHz
Sensitivity	FM: 2.5S μ V AM: 20 μ V
S/ N ratio	FM: 6.5dB AM: 50dB
Inputs sensitivity	Mic – 1~4 (balance) -50dB Mic – 1 (unbal.auto muting AUX-1AUX-2) AUX – 1 CD player -10dB AUX – 2 -20dB
CD player module	With MP3 reader function Channel: Output level: less than 2.0dB Frequency: $\pm 0.5/ - 1$ dB; $0 +/ - 1$ dB; $+/ - 2$ dB; $- 1 +/ - 2$ dB Separation rate: > 60 dB T.H.D.: $> 0.05\%$
Weight	11kg (24.25 lb)

