

Power Amplifiers

Specifications

PT9112

Max.output power		400 Wrms , 500 Wpeak
Built-in amplifier		Class D
Frequency response		20 Hz – 20 kHz
THD + N		0.01% @ 100W , 1 KHz , 4Ω
Efficiency		93% @ 350W , 1 KHz , 4Ω
Input impedance		Balanced : 20 kΩ Unbalanced : 10 kΩ
Min. speaker impedance		4Ω
Display (LED)		Power (green) Signal : 0 dBu (orange) , peak : +29 dBu (red)
Max. level	Input	Line : +30 dBu (24.5 V)
	Output	Speaker : +44 dBu (123 V)
Protection Functions		DC , over current , over voltage , Power on/off , short circuit
Connections (each power)		Balanced XLRs (M for Line out + F for line in Wired in parallel) , ¼" jack (for line in) , Speakon (Neutrik) & gold plated terminal (for audio out)
Cooling		Fan (automatic control : T>60°C ON , T<50°C OFF)
Power Source		210 -230 V~ , 50 – 60Hz
Dimensions (W×H×D)		19 × 3.5 × 11 inch (2U Rack mountable) 48.3 × 8.9 × 27.9 cm
Weight		7.8 kg

دفتر فروش : خیابان جمهوری اسلامی - چهارراه سی تیر - پاساژ فرقانی - طبقه دوم واحد 5 تلفن : 66724238 - 66722093

فکس : 66725702

دفتر مرکزی : میدان بهارستان - خیابان مجاهدین - خیابان ایران - پلاک 32 تلفن : 33562263 فکس : 33566792