

## Dual Power Amplifiers

Specifications		PT9212
Max.output power		2 × 400 Wrms , 2 × 500 Wpeak Each power can be used independently
Built-in amplifiers		2 × Class D
Frequency response		20 Hz – 20 kHz
THD + N		0.01% @ 100W , 1 KHz , 4Ω
Efficiency		93% @ 350W , 1 KHz , 4Ω
Input impedance		Balanced : 20 kΩ Unbalanced : 10 kΩ
Min. speaker impedance		4Ω
Display (LED , each power)		power (green) Signal : 0 dBu (orange) , peak : +29 dBu (red) Protect (blue)
Mode (select inputs)	Rear	Dual (A & B) or Parallel (B)
Max. level	Inputs	Line : +30 dBu (24.5 V)
	Outputs	speaker : +44 dBu (123 V)
Protection Functions		DC , over current , over voltage , Power on/off , short circuit
Connections (each power)		Balanced XLRs (M for Line out + F for line in Wired in parallel) , ¼” jack (for line in) , Speakon ( <i>Neutrik</i> ) & gold plated terminals ( for audio out )
Cooling		Fan ( automatic control : T>60°C ON , T<50°C OFF)
Power Source		210 -230 V~ , 50 – 60Hz
Dimensions (W×H×D)		19 × 3.5 × 15.5 inch (2U Rack mountable) 48.3 × 8.9 × 39.4 cm
Weight		12.5 kg

دفتر فروش : خیابان جمهوری اسلامی - چهارراه سی تیر - پاساژ فرقانی - طبقه دوم واحد 5 تلفن : 66722093 - 66724238

فکس : 66725702

دفتر مرکزی : میدان بهارستان - خیابان مجاهدین - خیابان ایران - پلاک 32 تلفن : 33562263 فکس : 33566792